

## U. S. COAST GUARD **MINIMUM** REQUIREMENTS FOR RECREATIONAL VESSELS

<b>EQUIPMENT</b>	<b>CLASS A</b> Less than 16ft/4.9m	<b>CLASS 1</b> 16 to less than 26 ft/7.9m	<b>CLASS 2</b> 26 to less than 40 ft/12.2m	<b>CLASS 3</b> 40 to not more than 65 ft/19.8m
<b>Personal Flotation Devices (PFDs)</b>	One approved Type I, II, III or V (must be worn) PFD for each person on board or being towed on water skis, tubes, etc.			
	One approved Type I, II or III PFD for each person on board or being towed on water skis, etc.; and one throwable Type IV device. ( A type V PFD may be used in lieu of any wearable PFD, if approved for the activity in which it is being used. <b>A TYPE V HYBRID MUST be worn to be legal.</b> )			
<b>Check state laws for PFD requirements for children and certain water craft &amp; sports.</b>				
<b>Bell or Whistle</b>  (HORN)	Every vessel less than 39.4 ft (12 meters) in length must carry an efficient sound producing device.		Every vessel 39.4 ft (12 meters) or larger in length must carry a whistle and a bell. The whistle must be audible for 1/2 nautical mile. The mouth of the bell must be at least 7.87 inches (200mm) in diameter.	
<b>Visual Distress Signals</b> (Coastal Waters, the Great Lakes & US owned boats on the high seas)	Required to carry approved visual distress signals for night-time use.	Must carry approved visual distress signals for both daytime and night-time use.  <b style="color: red; text-decoration: underline;">MINIMUM OF (3)</b>		
<b>Fire Extinguisher</b>  (Must be Coast Guard approved)	One B-I type approved hand portable fire extinguisher. (Not required on outboard motorboats less than 26 ft in length if the construction of the motorboat is such that it does not permit the entrapment of explosive or flammable gases or vapors and if fuel tanks are not permanently installed.)	Two B-I type <b>OR</b> one B-II type approved portable fire extinguishers.	Three B-I type <b>OR</b> one B-I type <b>PLUS</b> one B-II type approved portable fire extinguishers.	
<b>When a fixed fire extinguishing system is installed in machinery spaces it will replace one B-I portable fire extinguisher.</b>				
<b>Ventilation</b>  (Boats built on or after 8/1/80)	At least two ventilation ducts capable of efficiently ventilating every closed compartment that contains a gasoline engine and/or tank, except those having permanently installed tanks which vent outside of the boat and which contain no unprotected electrical devices. Engine compartments containing a gasoline engine with a cranking motor are additionally required to contain power operated exhaust blowers which can be controlled from the instrument panel.			
<b>Ventilation</b>  (Boats built before 8/1/80)	At least two ventilation ducts fitted with cowls (or their equivalent) for the purpose of efficiently and properly ventilating the bilges of every closed engine and fuel tank compartment using gasoline as fuel or other fuels having a flashpoint of 110 degrees or less. Applies to boats constructed or decked over after April 25, 1940.			
<b>Back-fire Flame Arrestor</b>	One approved device on each carburetor of all gasoline engines installed after April 25, 1940, except outboard motors.			

Note: Some states have requirements in addition to the federal requirements. Check your state's boating laws.

**BOATBOY MARINE TRAINING    (800) 493-9514    [www.boatboymarinetraining.com](http://www.boatboymarinetraining.com)**